



High Capacity

The WSE Commander, designed for operation at 70 tons per hour (depending on field and crop conditions), lowers harvesting costs by providing more production from each machine.

Greater Recovery

The Commander's patented recovery reel and 2-stage shaker system are unequaled at tomato recovery. There is simply no better combination to minimize harvest losses. Shaker frequency is easily controlled for optimal performance for any variety and in all conditions.

Clean Harvest

Two-way dirt belts, outfitted with 32 channel dirt sorters, are standard equipment. High efficiency, 30" direct driven suction fans remove loose vines and trash through 12" diameter tubes, provide the maximum airflow in the industry.

Operator Visibility & Controls

The operator platform is designed to provide the driver with clear visibility of the harvesting operation. Header controls are mounted on the steering column. Bulk loader, speed control, and other functions are located within easy reach to the right of the driver.

Maneuverability

The 225 hp 6068HFC08 Final Tier 4 John Deere engine, in conjunction with 4-wheel hydrostatic drive and 4-wheel steering results in an easy-to-maneuver, reliable machine with plenty of power to spare.

Long Life

Using the highest quality materials and a professional level of manufacturing ensures the harvester will produce for you now and into the future.

WSE COMMANDER TOMATO HARVESTER



STANDARD FEATURES

- 4-Wheel steering
- Automatic machine leveling
- Endless aftersort belts, 38" width
- Two-way dirt system conveyor, 32 channel
- Patented recovery reel for superior vine agitation
- Wheel Centers of 60, 63, 66, 70, 72, 76 or 80 available
- John Deere 6068HFC08 225 HP Final Tier 4
- Limited slip traction control system
- 30" rotor suction fans for superior performance
- Two 40 Channel colorsorts
- 32" wide rear cross deep reservoir for non-stop trailer transitions
- One man swing-away elevator
- 13.00 x 24 radial tires
- Fold-up catwalks for easy transport
- 3-Speed ground drive system
- Heavy duty 6000 psi ground drive motors for unsurpassed reliability and torque
- Long-life urethane coated shaker tines
- Remote grease banks
- LED lights

OPTIONAL FEATURES

- Sickle, Rod Weeder, Disc Pickup
- 2-Weight or 3-Weight Head
- Vine Shredder
- Dual Color Sort System
- Air Condition Cab
- Adjustable Axles

DIMENSIONS

- A.** Length: 36' 4" (11.07m)
- AA.** Transport Length: 41' 2" (12.55m)
- B.** Wheel Base: 12' 0" (3.66m)
- C.** Bulk Loader Dump Height
Standard: 12' 4" (3.76m)
Extended: 13' 0" (3.96m)
- D.** Bulk Loader Dump Width
Standard: 5' 6" (1.68m)
Extended: 7' 0" (2.13m)
- E.** Bulk Loader Leg: 10' 6" (3.20m)
- F.** Span from wheel
Standard: 18' 7" (5.66m)
Extended: 20' 1" (6.12m)
- G.** Header Width: 4' 7" (1.40m)
- H.** Width
Catwalks extended: 16' 8" (5.08m)
- I.** Wheel - Gauge
Standard: 5' 0" (1.52m)
Extended: 5' 6" (1.68m)
- J.** Width
Catwalks retracted: 14' 2" (4.32m)
- K.** Heights to Sunshade: 10' 1" (3.07m)
- L.** Overall Height: 10' 11" (3.33m)



Westside Equipment Madera

2500 W Industrial Avenue
Madera, CA 93637
Phone: (559) 577-1800
Fax: (559) 661-4694

Westside Equipment Crows Landing

18 Fink Road
Crows Landing, CA 95313
Phone: (209) 856-4700
Fax: (209) 837-4796

Westside Equipment Woodland

1230 Churchill Downs
Woodland, CA 95776
Phone: (530) 298-5035
Fax: (530) 666-3100

Westside Equipment Five Points

20289 W Oakland
Five Points, CA 93624
Phone: (559) 884-7700
Fax: (559) 884-7701

www.westsideequipment.com

